

Product Selection Guide

New products are frequently introduced. Please visit www.DeltaPSU.com for latest product updates.

Product Type	Series	Model Name	Phase	PFC	Output Voltage	Output Current	Output Power	Input Voltage Range
			1					
Panel Mount Power Supply	PMT2 • IEC 60335, IEC 61558 approvals • Low profile 30mm height	PMT-12V35W2BA□	●		12 V	3.0 A	36 W	90-264 V _{AC}
		PMT-12V50W2BA□	●			4.2 A	50.4 W	
		PMT-12V75W2BA□	●			6.0 A	72 W	
		PMT-12V100W2BA□	●			8.5 A	102 W	
		PMT-12V150W2BA□	●			12.5 A	150 W	90-132 V _{AC} , 180-264 V _{AC} (Selectable by Switch)
		PMT-12V150W2CA□	●			12.5 A	150 W	
		PMT-12V200W2BM□	●			17.0 A	204 W	90-132 V _{AC} , 180-264 V _{AC} (Selectable by Switch)
		PMT-12V200W2BR□	●			17.0 A	204 W	
		PMT-12V350W2BM□	●			29.0 A	348 W	
		PMT-12V350W2BR□	●			29.0 A	348 W	
		PMT-15V35W2BA	●		15 V	2.4 A	36 W	90-264 V _{AC}
		PMT-15V50W2BA	●			3.4 A	51 W	
		PMT-15V75W2BA	●			5.0 A	75 W	90-264 V _{AC}
		PMT-15V100W2BA	●			7.0 A	105 W	
		PMT-15V150W2BA	●			10.0 A	150 W	90-132 V _{AC} , 180-264 V _{AC} (Selectable by Switch)
		PMT-15V150W2CA	●			10.0 A	150 W	
		PMT-24V35W2BA□	●		24 V	1.5 A	36 W	90-264 V _{AC}
		PMT-24V50W2BA□	●			2.2 A	52.8 W	
		PMT-24V75W2BA□	●			3.2 A	76.8 W	
		PMT-24V100W2BA□	●			4.5 A	108 W	
		PMT-24V150W2BA□	●			6.25 A	150 W	90-132 V _{AC} , 180-264 V _{AC} (Selectable by Switch)
		PMT-24V150W2CA□	●			6.25 A	150 W	
		PMT-24V200W2BM□	●			8.8 A	211.2 W	90-132 V _{AC} , 180-264 V _{AC} (Selectable by Switch)
		PMT-24V200W2BR□	●			8.8 A	211.2 W	
		PMT-24V350W2BM□	●			14.6 A	350.4 W	
		PMT-24V350W2BR□	●			14.6 A	350.4 W	
		PMT-30V35W2BA	●		30 V	1.2 A	36 W	90-264 V _{AC}
		PMT-30V50W2BA	●			1.7 A	51 W	
		PMT-30V75W2BA	●			2.5 A	75 W	90-264 V _{AC}
		PMT-30V100W2BA	●			3.6 A	108 W	
		PMT-30V150W2BA	●			5.0 A	150 W	90-132 V _{AC} , 180-264 V _{AC} (Selectable by Switch)
		PMT-30V150W2CA	●			5.0 A	150 W	
		PMT-36V35W2BA	●		36 V	1.0 A	36 W	90-264 V _{AC}
		PMT-36V50W2BA	●			1.45 A	52.2 W	
		PMT-36V75W2BA	●			2.1 A	75.6 W	
		PMT-36V100W2BA	●			3.0 A	108 W	
		PMT-36V150W2BA	●			4.3 A	154.8 W	90-132 V _{AC} , 180-264 V _{AC} (Selectable by Switch)
		PMT-36V150W2CA	●			4.3 A	154.8 W	
		PMT-36V200W2BM	●			5.9 A	212.4 W	90-132 V _{AC} , 180-264 V _{AC} (Selectable by Switch)
		PMT-36V200W2BR	●			5.9 A	212.4 W	
		PMT-36V350W2BM	●			9.7 A	349.2 W	
		PMT-36V350W2BR	●			9.7 A	349.2 W	
		PMT-48V35W2BA	●		48 V	0.8 A	38.4 W	90-264 V _{AC}
		PMT-48V50W2BA	●			1.1 A	52.8 W	
		PMT-48V75W2BA	●			1.6 A	76.8 A	
		PMT-48V100W2BA	●			2.3 A	110.4 W	
		PMT-48V150W2BA	●			3.3 A	158.4 W	90-132 V _{AC} , 180-264 V _{AC} (Selectable by Switch)
		PMT-48V150W2CA	●			3.3 A	158.4 W	
		PMT-48V200W2BM	●			4.4 A	211.2 W	90-132 V _{AC} , 180-264 V _{AC} (Selectable by Switch)
		PMT-48V200W2BR	●			4.4 A	211.2 W	
		PMT-48V350W2BM	●			7.3 A	350.4 W	
		PMT-48V350W2BR	●			7.3 A	350.4 W	

Model Numbering

							CC Code
PM	T –	XXV	XXXW	2	□	□	□
Panel Mount	Product Type T - Enclosed	Output Voltage	Output Power	Single Phase with Low Profile	Family Code For 35-100W B - No PFC, universal input voltage range For 150-350W B - No PFC, input voltage selectable by switch C - No PFC, universal input voltage range	Connector Type Terminal Block A - With TUV, UL, CE, CCC, KC, EAC M - With UL, EAC R - With TUV, UL, CE, EAC	Blank - Without connector cover B - With conformal coating ¹⁾

| Product Selection Guide

New products are frequently introduced. Please visit www.DeltaPSU.com for latest product updates.

Product Type	Series	Model Name	Phase	PFC	Output Voltage	Output Current	Output Power	Input Voltage Range*
			1					
Panel Mount Power Supply	PMT2 • IEC 60335, IEC 61558 approvals • Low profile 30mm height	PMT-D1V75W2□A	•		5 V/12 V	5.0A/4.0A	73 W	90-264 V _{AC}
		PMT-D2V75W2□A	•		5 V/24 V	5.0A/2.1A	75.4 W	90-264 V _{AC}
	PMC • Universal AC input voltage	PMC-05V015W1AA	•		5 V	3.0 A	15 W	85-264 V _{AC} (DC input range 125-375 V _{DC})
		PMC-12V150W1B□	•	•	12 V	12.5 A	150 W	85-264 V _{AC} (DC input range 125-375 V _{DC})
		PMC-12V600W1BA	•	•		50.0 A	600 W	85-264 V _{AC} (DC input range 120-370 V _{DC})
		PMC-24V150W1B□	•	•	24 V	6.25 A	150 W	85-264 V _{AC} (DC input range 125-375 V _{DC})
		PMC-24V300W1BA	•	•		V1: 12.5 A V2 _{SB} : 0.5 A	300 W	
		PMC-24V600W1BA	•	•		25.0 A	600 W	85-264 V _{AC} (DC input range 120-370 V _{DC})
		PMC-24V600W1RW	•	•		25.0 A	600 W	85-264 V _{AC}
		PMC-48V150W1BA	•	•	48 V	3.125 A	150 W	85-264 V _{AC} (DC input range 125-375 V _{DC})
		PMC-48V600W1BA	•	•		12.5 A	600 W	85-264 V _{AC} (DC input range 120-370 V _{DC})
		PMC-DSPV100W1A	•		24 V/5 V	2.7 A/7.0 A	100 W	85-264 V _{AC} (DC input range 125-375 V _{DC})
	PMF • Remote ON/OFF • Built-in PFC	PMF-4V320WC□□	•	•	4.2 V	55.0 A	231 W	88-264 V _{AC}
		PMF-5V320WC□□	•	•	5 V	55.0 A	275 W	88-264 V _{AC}
		PMF-24V240WC□□	•	•	24 V	10.0 A	240 W	88-264 V _{AC}
		PMF-24V320WC□□	•	•		13.3 A	320 W	88-264 V _{AC}

* DC input is certified for selected models

Model Numbering

PM	T –	XXV	XXXW	2	□	A
Panel Mount	Product Type T - Enclosed	Output Voltage Dual Output D1 - 5 V / 12 V D2 - 5 V / 24 V	Output Power	Single Phase with Low Profile	Family Code B - No PFC, Non-Isolated C - No PFC, Isolated	Connector Type A - Terminal Block

1) Options for 12 V and 24 V models only

PM	C –	XXV	XXXW	1	□	□
Panel Mount	Product Type C - Enclosed	Output Voltage	Output Power	Phase Input 1 - Single Phase, Wide Range Input Voltage	A - No PFC B - With PFC R - With PFC, Remote ON/OFF, Remote Sense	Connector Type A - Terminal Block ¹⁾ J - IP20 Connector ²⁾ L - Front Face ²⁾ W - Front Face with conformal coating
PM	C –	D	SPV	100W	1	A
Panel Mount	Product Type C - Enclosed	Dual Output	Output Voltage S - 24V P - 5V	Output Power	Phase Input 1 - Single Phase	A - Delta Standard

1) For PMC-05V015W1AA and PMC-□V600W1BA, the connector type is a Front Face connector. For PMC-24V300W1BA, the connector type is an IP20 connector.

2) Options

PM	F –	XXV	XXXW	C	□	□
Panel Mount	Product Series F - PFC Series	Output Voltage	Output Power	Package Type C - Enclosed	Connector Type G - Front Face A - Terminal Block ¹⁾	Variable B - No Remote ON/OFF R - With Remote ON/OFF ¹⁾

1) Options

Product Selection Guide

New products are frequently introduced. Please visit www.DeltaPSU.com for latest product updates.

Product Type	Series	Model Name	Phase	PFC	Output Voltage	Output Current	Output Power	Input Voltage Range*
			1					
Panel Mount Power Supply	PMH • IEC 60335, IEC 61558 approvals • Withstand line input voltage surge 300Vac up to 7 seconds • Low profile (for selected models)	PMH-24V50WCA□	●		24 V	2.1 A	50 W	85-264 V _{AC} (DC input range 120-375 V _{DC})
		PMH-24V100WCA□	●			4.16 A	100 W	
		PMH-24V150WCB□	●	●		6.25 A	150 W	85-264 V _{AC} (DC input range 120-375 V _{DC})
		PMH-24V150WCD□	●	●		6.25 A	150 W	
		PMH-24V200WCB□	●	●		8.33 A	200 W	
		PMH-12V100WCM□	●		12 V	8.5 A	100 W	85-264 V _{AC} (DC input range 120-375 V _{DC})
		PMH-24V100WCL□	●		24 V	4.5 A	100 W	
		PMH-24V100WCM□	●			3.8 A	91.2 W	
		PMH-24V150WCL□	●			6.5 A	150 W	
		PMH-24V150WCL□	●			6.5 A	150 W	
	PMR • Thickness < 1U • Built-in PFC	PMR-4V320WCA□	●	●	4.2 V	60.0 A	252 W	88-264 V _{AC}
		PMR-4V320WDAA	●	●		60.0 A	252 W	
		PMR-4V320WDGA	●	●		60.0 A	252 W	
		PMR-4V320WDBA	●	●		60.0 A	252 W	
		PMR-4V320WDCA	●	●		60.0 A	252 W	
		PMR-5V320WCA□	●	●	5 V	60.0 A	300 W	88-264 V _{AC}
		PMR-5V320WDAA	●	●		60.0 A	300 W	
		PMR-5V320WDGA	●	●		60.0 A	300 W	
		PMR-5V320WDBA	●	●		60.0 A	300 W	
		PMR-5V320WDCA	●	●		60.0 A	300 W	
		NEW PMR-12V320W1AT	●	●	12 V	26.7 A	320.4 W	90-264 V _{AC}
		NEW PMR-24V320W1AT	●	●	24 V	13.4 A	321.6 W	90-264 V _{AC}
		NEW PMR-36V320W1AT	●	●	36 V	8.9 A	320.4 W	90-264 V _{AC}
		NEW PMR-48V320W1AT	●	●	48 V	6.7 A	321.6 W	90-264 V _{AC}

* DC input is certified for selected models

Model Numbering

PM	H –	XXV	XXXW	C	□	□
Panel Mount	Product Series H - Household Series	Output Voltage	Output Power	Package Type C - Enclosed	Pollution Degree 2 A - No PFC B - With PFC Pollution Degree 3 D - With PFC L - Low Profile M - Low Profile with NEC Class 2	Output Non-Isolated to PE (PELV) A - Terminal Block ¹⁾ L - Front Face ²⁾ H - Harness ¹⁾ Output Isolated to PE (SELV) S - Terminal Block T - Harness

1) Options for all models excluding low profile (PMH-12V100WCM□, PMH-24V100WCL□, PMH-24V100WCM□, PMH-24V150WCL□)

2) Options for PMH-24V200WCB□ only

PM	R –	XXV	XXXW	□	□	A
Panel Mount	Product Series R - Standard Rack Type Series (1U)	Output Voltage	Output Power	Package Type C - Enclosed with Fan D - Enclosed without Fan	Connector Type A - Terminal Block B - Terminal Block (Parallel Operation) ¹⁾ G - Front Face ²⁾ C - Front Face (Parallel Operation) ¹⁾	Variable A - With conformal coating

1) Options for Enclosed without Fan (PMR-□V320WDBA and PMR-□V320WDCA)

2) Options

PM	R –	XXV	XXXW	1	A	T
Panel Mount	Product Series R - Standard Rack Type Series (1U)	Output Voltage	Output Power	Phase Input 1 - Single Phase	Family Code A - Family A	Variable T - Terminal Block

| Product Selection Guide

New products are frequently introduced. Please visit www.DeltaPSU.com for latest product updates.

Product Type	Series	Model Name	Phase	PFC	Output Voltage	Output Current	Output Power	Input Voltage Range
			1					
Panel Mount Power Supply	MEB • Intelligent Fan Speed Control	NEW MEB-750A12B AAA	●	●	12 V	58.4 A	750 W	85-264 V _{AC}
		MEB-750A12T AAA	●	●		58.4 A	750 W	
		MEB-500A24F AA	●	●	24 V	21.0 A	500 W	90-264 V _{AC}
		MEB-750A24B AAA	●	●		31.25 A	750 W	85-264 V _{AC}
		MEB-750A24T AAA	●	●		31.25 A	750 W	
		MEB-750A48B AAA	●	●	48 V	15.63 A	750 W	85-264 V _{AC}
		MEB-750A48T AAA	●	●		15.63 A	750 W	
		MEB-1K2A24T ABA	●	●	24 V	50.0 A	1,200 W	85-264 V _{AC}
		MEB-1K2A42T ABA	●	●	42 V	28.5 A	1,200 W	85-264 V _{AC}
		MEB-1K2A48T ABA	●	●	48 V	25.0 A	1,200 W	85-264 V _{AC}

Model Numbering

ME	B –	XXX	A	□	□	□□□
Delta Medical Power Supply	B - Enclosed	Max power wattage in the product series. May be lower at some conditions.	Family Code	Output Voltage	Input Connector Type	CC Code
		500 - 500 W	A - Family A	24 - 24 V	F - Front Face	AA - With Remote ON/OFF, with conformal coating
		750 - 750 W		12 - 12 V 24 - 24 V 48 - 48 V	B - C14 T - US Terminal	AAA - With Remote ON/OFF, with conformal coating
		1K2 - 1,200 W		24 - 24 V 42 - 42 V 48 - 48 V	T - US Terminal	ABA - With Remote ON/OFF, with conformal coating